

**TOUGHER. FASTER. SMARTER.**

- **PIN-LESS IMPACT MECHANISM WITH ADVANCED HEAT TREATMENT MAXIMIZES TOOL LIFE**
- **SMOOTH RECOIL MECHANISM CREATES NO TORQUE REACTION**



**ALUMINUM HOUSING**

Provides Robust Durability while Minimizing Tool Weight

**METAL BELT CLIP**

for Workplace Convenience

**SOLID GRIP**

Provides Superior Protection against Slip, Chemicals, and Vibration.

**FOUR-POSITION SPEED ADJUSTMENT**

Provides Precise Speed Control

**ONE-HAND FORWARD/REVERSE LEVER**

Boosts Control and Stability for Left- and Right-Handed Users

**360° ADJUSTABLE EXHAUST**

Ensures Workplace Comfort

**DRIVE SPECIFICATION**

<b>Free Speed:</b>	10,000 rpm
<b>Max Torque:</b>	840 in-lbs (95 Nm)
<b>Working Torque:</b>	120~780 in-lbs (14~88 Nm)
<b>Energy:</b>	0.4 HP
<b>Air Inlet:</b>	1/4" PT-19 or NPT-18
<b>Avg. Air Consumption:</b>	25 CFM (708 L/min)

**TOOL SPECIFICATION**

<b>Weight:</b>	2.2lbs. (1.0kg)
<b>Height:</b>	6.5" (164mm)
<b>Width:</b>	2.3" (58mm)
<b>Length:</b>	6.0" (153mm)
<b>Operating Pressure:</b>	90 psi (6.2 Bar)
<b>Actuation Mode:</b>	Trigger Actuated
<b>Applications:</b>	Wood Screws, Wall Boards Assembly Line Work

